

DURELASTIC

Pigment Paste 350-DURPaste

- Binder based on unsaturated polyester resin, styrene-free
- High concentration
- High colouring power
- Good to very good light resistance

| | | |
|-----------------------------------|---|--|
| Technical / Physical data | Colour | acc. to RAL 840 HR, other colour shades on request |
| | Original viscosity | fluidly to pasty (pigment-dependently) |
| | Density | 1,2 to 2,2 g / ml + / - 0,1 calculated |
| Storability | Approx. 11 month in original packings at an ambient temperature of 15 to 25 °C, in case the original packings are tightly closed. Opened packing must be used very shortly. The minimum storage stability of each batch is mentioned on the product label. A storage time beyond the mentioned date doesn't necessarily mean that the material is | |
| Processing and application | Application, Addition of | in original viscosity 2 to 5 % for colouring of resins 10 to 15 % for colouring of top coat resins |
| | Cleaning of working equipment | EFD-Cleaning agent 400906 |
| Special remarks | Advise for safety protection and protection of health The usual precautionary measures for ventilation as well as for personal protection are to be observed when handling painting materials. Detailed information about dangerous goods, sayfety data and recommendations concerning health protection and environment protection can be read in the corresponding safety data sheet. | |
| | Preliminary tests accomplish. Dependent on the colour the pigments can the pot life shorten or extend | |
| | Test conditions All information is based on a standard climate 20/65 DIN 50014. The information about economy and characteristics dependent on colour. The information in this data sheet are reference values and are not given as specification. | |