



BD7593XRU999

DURELASTIC-Wax-Additive 5 %

General product properties

Colour	colorless	
Viscosity	Flow time 12 - 15 sec., 4 mm flow cup	DIN 53211
Density	0,8 +/- 0,05 g/ml	theoretical
Solid mass	ca. 5 %	theoretical
Resistance to storage	<p>approx. 6 month in original packagings at an ambient temperature of 5 to 25 °C. Open packages are to be used within a short time.</p> <p>The minimum storage stability of each batch is stated on the product label. The material does not necessarily become unusable if stored for longer than this period. However, for quality assurance purposes, an inspection of these materials is essential to ensure that they are still suitable for the intended application.</p>	

Application and processing

Note before use	Prior to use, stir well or mix components homogeneously (e.g. with fast mixer).
Mixin ratio	Products BD7593XRU999 Parts by weight 0,5 - 2,0 %
Thinning	EFD dilution 400900
Cleaning of equipment	with EFD cleaning agent 400906 within the processing time.

Further processing of coated pieces

Repainting	possible based on pre-test
-------------------	----------------------------

Comments

Work-and Healthprotection	The standard personal safety precautions must be observed when handling painting materials. Detailed information about dangerous goods, safety data and recommendations concerning Health and Safety at Work and environmental protection can be found in the corresponding safety data sheet.
Test conditions	<p>All information is based on a standard climate 23/50 DIN EN 23270. All information is based on our product knowledge an experience. We have no direct influence on the application itself. Please do not hesitate to contact us for further information.</p> <p>The information provided here contains reference values and does not constitute a specification.</p>