



## UR1025H\_HU0010\_METALLIC EFDEDUR-HighSolid-Metallic

### Product description

|                            |                                                                  |
|----------------------------|------------------------------------------------------------------|
| <b>Product technology</b>  | solvent-based 2-component coating                                |
| <b>Application area</b>    | e.g. in the mechanical engineering and plant construction sector |
| <b>Application</b>         | For interior and exterior applications                           |
| <b>Blocking resistance</b> | good                                                             |
| <b>Substrate</b>           | Steel, Galvanised steel                                          |

### General product properties

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |             |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| <b>Binder-Base</b>             | Acrylic Resin                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |             |
| <b>Colour</b>                  | RAL9006 White aluminium                                                                                                                                                                                                                                                                                                                                                                                                                                                          |             |
| <b>Viscosity</b>               | Flow time 25-55 sec., 4 mm flow cup                                                                                                                                                                                                                                                                                                                                                                                                                                              | DIN 53211   |
| <b>Density</b>                 | 0,8-1,2 g/ml after addition of hardener                                                                                                                                                                                                                                                                                                                                                                                                                                          | theoretical |
| <b>Solid mass</b>              | 49-55 % after addition of hardener                                                                                                                                                                                                                                                                                                                                                                                                                                               | theoretical |
| <b>Solid content in volume</b> | 53,5-58,5 % after addition of hardener                                                                                                                                                                                                                                                                                                                                                                                                                                           | theoretical |
| <b>Reference product</b>       | The specified values refer to the product UR1025HRA906.                                                                                                                                                                                                                                                                                                                                                                                                                          |             |
| <b>Resistance to storage</b>   | <p>approx. 9 month in original packagings at an ambient temperature of 5 to 25 °C. Open packages are to be used within a short time.</p> <p>The minimum storage stability of each batch is stated on the product label. The material does not necessarily become unusable if stored for longer than this period. However, for quality assurance purposes, an inspection of these materials is essential to ensure that they are still suitable for the intended application.</p> |             |

### Application and processing

|                                 |                                                                                                                                                                                                                                                                                                                               |                                                                |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>Pretreatment</b>             | The substrate must be free of adhesion-impairing substances such as oil, grease, rust, scale, mill scale, wax and release agent residues. We recommend the use of suitable mechanical pre-treatment processes (e.g. blasting, grinding) or chemical pre-treatment processes (e.g. phosphating) according to the requirements. |                                                                |
| <b>Structure recommendation</b> | Substrate                                                                                                                                                                                                                                                                                                                     | On blasted steel plate                                         |
|                                 | Primer                                                                                                                                                                                                                                                                                                                        | UR1937HRU735<br>Coating thickness 60-80 µm µm                  |
|                                 | Top coat                                                                                                                                                                                                                                                                                                                      | UR1025H<br>Mixing ratio 5:1 HU0010<br>Dry film thickness 30 µm |



## UR1025H\_HU0010\_METALLIC EFDEDUR-HighSolid-Metallic

|                               |                                                                                                                                                                          |                   |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| <b>Note before use</b>        | Prior to use, stir well or mix components homogeneously (e.g. with fast mixer).                                                                                          |                   |
| <b>Hardener</b>               | HU0010                                                                                                                                                                   |                   |
| <b>Mixin ratio</b>            | Parts by weight 5:1<br>Volume parts 5:1                                                                                                                                  |                   |
| <b>Thinning</b>               | EFD dilution 400500                                                                                                                                                      |                   |
| <b>Processing conditions</b>  | from 10 °C to 25 °C                                                                                                                                                      |                   |
| <b>Processing time</b>        | max. 2 hrs. / 20 °C<br>The processing time can decrease at higher temperatures and/or under pressure.                                                                    |                   |
| <b>High pressure spraying</b> | Set to 16-20 sec / 4 mm flow-cup after adding hardener<br>Nozzle 1,2-1,8 mm<br>Spray pressure 3-4 bar                                                                    | DIN 53211         |
| <b>Rolling/painting</b>       | as delivered viscosity after curing agent addition<br>Add 0,5 to 1,0% by wight EFD-Relaxation agent 300807 for roller and brush application in case of bubble formation. |                   |
| <b>Material usage</b>         | without application loss 50-60 g/m <sup>2</sup><br>layer thickness 20-30 µm after addition of hardener                                                                   | theoretical       |
| <b>Oven drying</b>            | up to 80 °C possible (object temperature)                                                                                                                                |                   |
| <b>Air drying</b>             | 20 °C, 50 % relative humidity                                                                                                                                            |                   |
| <b>Dust drying</b>            | after 20 minutes (degree of dryness 1)                                                                                                                                   | DIN EN ISO 9117-5 |
| <b>Dry to the touch</b>       | after 1,5 hours (degree of dryness 4)                                                                                                                                    | DIN EN ISO 9117-5 |
| <b>Full drying</b>            | after 14 day/s (pendulum damping)                                                                                                                                        | DIN EN ISO 1522   |
| <b>Cleaning of equipment</b>  | EFD dilution 400500                                                                                                                                                      |                   |

### Further processing of coated pieces

|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| <b>Repainting</b> | possible with same quality, dry at the earliest after matting. |
|-------------------|----------------------------------------------------------------|

### Comments

|                                  |                                                                                                                                                                                                                                                                                                                                                                  |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EFD info</b>                  | Further technical information can be found in the EFD Info. No. 170.                                                                                                                                                                                                                                                                                             |
| <b>Work-and Healthprotection</b> | The standard personal safety precautions must be observed when handling painting materials. Detailed information about dangerous goods, safety data and recommendations concerning Health and Safety at Work and environmental protection can be found in the corresponding safety data sheet.                                                                   |
| <b>Test conditions</b>           | All information is based on a standard climate 23/50 DIN EN 23270. All information is based on our product knowledge an experience. We have no direct influence on the application itself. Please do not hesitate to contact us for further information.<br><br>The information provided here contains reference values and does not constitute a specification. |