

DURELASTIC

Amin-Accelerator BD7560XRU999

- Accelerator for BP-hardenable systems

Technical / Physical data	Colour	yellowish
	Original viscosity	approx. 450 m.Pa.s
	Addition quantity (by weight)	0,1 to 1,0 % , as required
	Thinner	DURELASTIC-Resin-Thinner 400900
	Density calculated	1,0 g / ml + / - 0,05
	Solid content calculated	approx. 70 %
Storability	Approx. 6 month in original packings at an ambient temperature of 15 to 25 °C, in case the original packings are tightly closed. Opened packing must be used very shortly. The minimum storage stability of each batch is mentioned on the product label. A storage time beyond the mentioned date doesn't necessarily mean that the material is unusable. In this case a check of the qualities which are important for the respective.	
Processing and application	Processing	The accelerator addition depends on the respective use. <u>Attention:</u> Accelerators BD7560XRU999 and hardener separately mix and store!
	Cleaning of working equipment	EFD-Cleaner 400906
	Advise for safety protection and protection of health	The usual precautionary measures for ventilation as well as for personal protection are to be observed when handling painting materials. Detailed information about dangerous goods, safety data and recommendations concerning health protection and environment protection can be read in the corresponding safety data sheet.
Special remarks	Test conditions	All information is based on a standard climate 20/65 DIN 50014.
		All information are based on our product knowledge and experience. To the application we have no direct influence. For further information please don't hesitate to contact us.
		The information mentioned herein are reference values and are not given as specification.