

DURELASTIC

UP-Resin
BD7746XRU999

- UP-Resin based on unsaturated polyester
- Accelerator-free, styrene free

Technical / Physical data	Colour	colorless
	Original viscosity	appr. 500 m.Pa.s DIN 53015
	Thinner	DURELASTIC-Resin solution 400900
	Density calculated	1,1 g / ml + / - 0,1
	Solid content calculated	100 %
Storability	Approx. 6 month in original packings at an ambient temperature of 15 to 25 °C, in case the original packings are tightly closed. Opened packing must be used very shortly. The minimum storage stability of each batch is mentioned on the product label. A storage time beyond the mentioned date doesn't necessarily mean that the material is unusable. In this case a check of the qualities which are important for the respective	
Processing and application	Application	Components are to be mixed homogenously. Can be applied in original viscosity or after adjustment of viscosity with DURELASTIC- Resin solution 400900. Use as a thinner for pastes.
	Cleaning of working equipment	Within the working time with EFD-cleaning agent 400906.
	Advise for safety protection and protection of health	The usual precautionary measures for ventilation as well as for personal protection are to be observed when handling painting materials. Detailed information about dangerous goods, sayfety data and recommendations concerning health protection and environment protection can be read in the corresponding safety data sheet.
Special remarks	Test conditions	All information is based on a standard climate 20/65 DIN 50014, the information about economy and characteristics dependent on colour.
		All information are based on our product knowledge and experience. To the application we have no direct influence. For further information please don't hesitate to contact us.
		The information mentioned herein are reference values and are not given as specification.